

KORY RUNNING GEAR means big load hauling with rugged dependability. For years this running gear has proven itself "best in the field". It provides maximum stability, short turning radius, auto type steering and heavy duty tapered roller bearings. Unique Kory tow-bar is adjustable to a variety of lengths. Strong box girder design and heavy duty reach braces provide excellent strength for big loads. All are designed for non-highway use at tractor speeds.



SPECIFICATIONS

| CAPACITY | 5 TON MODEL 5566 | 6 TON MODEL 6672 | 8 TON MODEL 6872 | 8T-WIDE TRACK MODEL 6892 | 10 TON MODEL 6072 | 10T-WIDE TRACK MODEL 6092 |
|--------------------------------------|---|---|--|--|---|---|
| TREAD | 66" | 72" | 72" | 92" | 72" | 92" |
| AXLES | 3 x 5 x 10 GA Structural Steel Tubing | 3 x 6 x 10 GA Structural Steel Tubing | 3 x 6 x 3/16" Structural Steel Tubing | 3 x 6 x 3/16" Structural Steel Tubing | 4 x 8 x 3/16" Structural Steel Tubing | 4 x 8 x 3/16" Structural Steel Tubing |
| REACH | 2 1/2" x .140 Wall x 6' | 2 1/2" x .140 Wall x 6' | 3" x 3/16" Wall x 6' | 3" x 3/16" Wall x 6' | 3" x 3/16" Wall x 6' | 3" x 3/16" Wall x 6' |
| 6' REACH (STD.) | 77 1/2" x 117 1/2" | 77 1/2" x 117 1/2" | 77 1/2" x 117 1/2" | 77 1/2" x 117 1/2" | 77 1/2" x 117 1/2" | 77 1/2" x 117 1/2" |
| 8' REACH (OPT.) | 101 1/2" x 141 1/2" | 101 1/2" x 141 1/2" | 101 1/2" x 141 1/2" | 101 1/2" x 141 1/2" | 101 1/2" x 141 1/2" | 101 1/2" x 141 1/2" |
| 12' REACH (OPT.) | 149 1/2" x 189 1/2" | 149 1/2" x 189 1/2" | 149 1/2" x 189 1/2" | 149 1/2" x 189 1/2" | 149 1/2" x 189 1/2" | 149 1/2" x 189 1/2" |
| TIE RODS | 5/8" Rod | 1" x 3/32" Wall Steel Tubing | 1" x 3/32" Wall Steel Tubing | 1 1/4" x 3/32" Wall Steel Tubing | 1" x 3/32" Wall Steel Tubing | 1 1/4" x 3/32" Wall Steel Tubing |
| TIE ROD ENDS | Clevis Type | Truck Type | Truck Type | Heavy Duty Truck Type | Truck Type | Heavy Duty Truck Type |
| SPINDLES | 1 3/8" Carbon Steel | 1 5/8" Carbon Steel | 1 3/4" Carbon Steel | 1 3/4" Carbon Steel | 2" Carbon Steel | 2" Carbon Steel |
| BEARINGS | Tapered Roller Inner & Outer | Tapered Roller Inner & Outer | Tapered Roller Inner & Outer | Tapered Roller Inner & Outer | Tapered Roller Inner & Outer | Tapered Roller Inner & Outer |
| HUBS | Heavy Duty 5 bolt Press Fit Studs & nuts | Heavy Duty 6 Bolt Press Fit Studs & nuts | Heavy Duty 6 Bolt | Heavy Duty 6 Bolt | Heavy Duty 6 Bolt | Heavy Duty 6 Bolt |
| BOLSTER STAKES | 12 Ga. Adj. 38" x42" | 10 Ga. Adj. 38" x42" | 10 Ga. Adj. 38" x42" | 10 Ga. Adj. 38" x42" | 7 Ga. Adj. 38" x 42" | 7 Ga. Adj. 38" x 42" |
| OPTIONAL WHEELS | 5 x 15 | 6 x 15, 6 x 16 | 6 x 15, 6 x 16, 8 x 15, 8 x 16 | 6 x 15, 6 x 16, 8 x 15, 8 x 16 | 6 x 15, 6 x 16, 8 x 15, 8 x 16, 10 x15, 10 x 16, 8.25 X 22.5 | 6 x 15, 6 x 16, 8 x 15, 8 x 16, 10 x15,10 x16, 8.25 X 22.5 |
| OPTIONAL TONGUE (specs below) | 5T5 5 ton standard | S100 Standard A100 Adjustable | S100 Standard A100 Adjustable | S100 Standard A100 Adjustable | S100 Standard A100 Adjustable | S100 Standard A100 Adjustable |
| WEIGHT WITH RIMS & TONGUE(APPR**) | 340 LBS | 450 LBS | 500 LBS | 550 LBS | 625 LBS | 675 LBS |

** WEIGHTS VARY WITH CHOICE OF TONGUE AND RIM SIZE

| | |
|--------------------|---|
| 5T5 tongue | Formed 7" Steel, Tapered Channel, 65" Drawbar, Eye & King Pin |
| S100 tongue | Extra Heavy, Formed 7" Steel Tapered channel, 65" Drawbar, Eye & King Pin |
| A100 tongue | Heavy Duty, Quick Hitch 7/8" King pin, 7" tapered, 73" adjusts to 93" |

KORY FARM EQUIPMENT, LLC

P.O. Box 349 , Manlius, IL 61338 Phone (815) 445-3711, Fax (815) 445-5141
www.koryfarm.com